



**WORKS WITH
EXTERNAL LED
DRIVER**
(24V Constant Voltage)
Sold Separately



IDEAL FOR

Curved glass display cases, freezer & cooler doors, display cases with tight space requirements, corners, shelves, cosmetic counters, makeup & jewelry displays

SPECIFICATIONS

Available in 16ft (5m) Rolls
IP67
SMD 2835 LED
72W (16ft/5m Roll)
14.4W/m
463.5lm/f
Cutttable (Marked on LED Tape)
Joinable (Using Connector)
120° Beam Angle
24V Driver/Transformer
Rated life: 50 000 hrs
Voltage input: DC 24V

Model Number	Watts	Lumens (16ft Roll)	Lumens per Watt	Color
FLEX24-PL-72-16	72	7416	103	Platinum
FLEX-PW-16-55 (12V)	55	5280	96	Premium White
FLEX24-RW4-60-16	60	6160	103	RW4

ACCESSORIES

Included



1. Female DC 5mm Power Cord
2. Silicone End-Cap
3. Silicone Mounting Clip
4. Connector
5. M to F DC 5mm Power Splitter
6. M to F 39" DC 5mm Extnsn Cord
7. M to F 8" DC 5mm Extnsn Cord
8. Corner Connector
9. Male DC 5mm Cord

Optional Purchase



OPERATING CONDITIONS

Secures With: 3M™ High-Strength Acrylic Adhesive 300LSE
Storage temperature: -40°C to 80°C
Operating Temperature: -25°C to 60°C
Working Voltage: DC 24V
Installation surface must be smooth, clean & dry
Do not exceed 16ft length per DC 24V Driver

