



T5 EXTERNAL DRIVER LED

CE ETL US RoHS c UL US
Driver: E477240

WORKS WITH EXTERNAL LED DRIVER
 (24V Constant Voltage)
Sold Separately



IDEAL FOR

Service & Multi-Deck: Meat, Seafood, Dairy, Deli, Prepared & Frozen Foods, Floral, Produce, Bakery, Salad Bars & Ice Cream/Gelato

SPECIFICATIONS

- G5 Bi-Pin End-Caps
- External Power Supply (External Driver)
- IP55
- Replaces T5 Fluorescent Tubes
- Double End Power Input (Polar)
- 180° Beam Angle
- DC 24V
- UL Conforming
- High Brightness/ 80 CRI
- Up to 60% Energy savings
- Average 50,000 Hours Life Span
- 5 Year Warranty

Size	Model Number	Watts	Type	Length (mm) (Nominal)	Length (in) (Nominal)	Replaces Fluorescent	Lumens	Lumens per Watt	Color
1ft	T5-PL-10C+*	7	Canopy	249	10	F8 T5	785	115	Platinum
2ft	T5-PL-22C+*	8	Canopy	549	22	F14 T5	880	110	Platinum
3ft	T5-PL-34C+*	10	Canopy	849	34	F21 T5	1582	113	Platinum
4ft	T5-PL-46C+*	15	Canopy	1149	46	F28 T5	2070	115	Platinum
5ft	T5-PL-58C+*	20	Canopy	1449	58	F35 T5	2508	114	Platinum
3ft	T5-PL-34S+*	5	Shelf	849	34	F21 T5	791	113	Platinum
4ft	T5-PL-46S+*	8	Shelf	1149	46	F28 T5	1035	115	Platinum

* T5-PL-XXC+ (& S+) Replaces Previous Model Number: T5-PL-XXC (& S)
 Stock with original model numbers available while supplies last

